



**CLARIFIZE®** is a proprietary blend of Pure-Line Flocculent that entraps solids in water and quickly drops them to the bottom.

**APPLICATIONS:** Excellent for dropping suspended solids in slurry water, allowing the resulting clear water to be recycled or safely disposed of.

**Concrete Saw Cutting | Concrete Polishing | Concrete Washout Pits | Masonry | Industrial Water**

**DIRECTIONS FOR USE:** Broadcast **CLARIFIZE®** across the top of the liquid. Stir or agitate well. Wait several minutes and then stir again. Depending on your material, it may be necessary to apply additional **CLARIFIZE®** and / or allow additional time for the reaction to take place. When solids have dropped you may pump or decant the clear water for reuse or adjust PH, if necessary, for proper disposal down a regular sanitary sewer drain. The remaining high-solids sludge can then be treated with **CONGELZ®** allowing safe and legal disposal as a non-hazardous solid, passing ASTM 9095B Paint Filter Test.

**NOTES:** **CLARIFIZE®** works best when solids are less than 30%. If solids are significantly higher, you may simply use **CONGELZ®** to solidify the entire slurry. If the solids content is too high, then the material will simply not separate. In this case the addition of more material will only cause the slurry to become thick and stringy. If your slurry is separating nicely but the water has a slimy feel to it, there is simply excess polymer available to drop more solids; lower the dose as necessary.

**COVERAGE:** Coverage for each product will vary depending on the solids content in the water.

| CONGELZ | Qty of Slurry | Treated Slurry Remains** | Fresh Slurry *      |
|---------|---------------|--------------------------|---------------------|
|         | 1 gallon      | 1/3 OZ – 1 OZ            | 0.8 OZ – 1 OZ       |
|         | 5 gallons     | 1-3/4 OZ – 5 OZ          | 4 OZ – 5 OZ         |
|         | 55 gallons    | 1-1/4 – 4 lbs            | 2-3/4 lb – 3-1/2 lb |

\* Coverage will vary depending on solids content in the slurry

\*\* After dropping solids with Clarifize and draining clear water

| CLARIFIZE | Quantity              | Fresh Slurry * |
|-----------|-----------------------|----------------|
|           | 4 gr. – 1/4 OZ        | 1 gallon       |
|           | 1/2 OZ – 1-1/4 OZ     | 5 gallon       |
|           | 1/3 lb – 1 lb         | 55 gallon      |
| 40 lb box | 2,200 – 6,600 gallons |                |

**PRECAUTIONS:** Normally there is no need for special handling precautions.

**FIRST AID:** If eye contact occurs, flush eyes with water for a minimum of fifteen (15) minutes. Remove from skin with soap and water.

**TECHNICAL ASSISTANCE:** Visit us at [www.congelz.com](http://www.congelz.com) or call us at 888-440-4250

**WARRANTIES:** Seller warrants that its products will conform to and perform in accordance with the products specifications. This foregoing warranty is in lieu of all other warranties, expressed or implied, including, but not limited to, those concerning merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, except for claims for bodily injury, Seller's liability to the Buyer or any third party, arising out of the purchase of the product from Seller by Buyer shall not exceed the total amount billed and billable to the Buyer for the product hereunder.

